# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 1 of 11

Revision date: 29.11.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

KaVo QUATTROcare plus Spray

#### Product code:

1.005.3843 1.005.4525

## **Further trade names**

QUATTROcare plus Spray 2140, QUATTROcare plus Spray 2140P

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricating agent

## 1.3. Details of the supplier of the safety data sheet

Company name: KaVo Dental GmbH Street: Bismarckring 39 Place: D-88400 Biberach

Telephone: +49 (0) 7351 56 0 Telefax: + 49 (0) 7351 56 1488

e-mail: sdb@kavo.com

e-mail (Contact person): support@gefahrstoff.com

Internet: www.kavo.com

Responsible Department: Questions concerning SDB: PES-Ingenieurgesellschaft mbH

**1.4. Emergency telephone** +49 (0) 7351 56 4000 (24 h)

number:

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

## 2.2. Label elements

# Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



# **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 2 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification	•	•			
106-97-8	butane			25 - < 50 %		
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1, Liquefied (	gas; H220 H280	•			
75-28-5	isobutane			25 - < 50 %		
	200-857-2	601-004-00-0	01-2119485395-27			
	Flam. Gas 1, Liquefied (	gas; H220 H280				
8042-47-5	White mineral oil (petrol	eum)		10 - < 20 %		
	232-455-8		01-2119487078-27			
	Asp. Tox. 1; H304					
74-98-6	propane			5 - < 10 %		
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1, Liquefied (					

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with skin

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

# After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 3 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness. May cause drowsiness or dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms can occur only after several hours.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder. Water mist.

Co-ordinate fire-fighting measures to the fire surroundings.

## Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

In case of fire may be liberated: Gases/vapours, toxic (Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black)

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protective suit. In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Remove persons to safety. Evacuate area. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

# 6.3. Methods and material for containment and cleaning up

Ventilate affected area. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



Page 4 of 11

Revision date: 29.11.2019

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use. Do not pierce or burn, even after use. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Wear personal protection equipment.

#### Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

## Further information on storage conditions

Protect against: frost. Protect against direct sunlight. Protect from sunlight.

## 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

# 8.2. Exposure controls







#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Protective and hygiene measures

Take off contaminated clothing. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray.

#### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

# **Safety Data Sheet**

K4VO

Dental Excellence

according to Regulation (EC) No 1907/2006

Page 5 of 11

Revision date: 29.11.2019

## Hand protection

Wear suitable gloves. EN ISO 374

Protect skin by using skin protective cream.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protect skin by using skin protective cream.

Suitable material: NBR (Nitrile rubber)

Breakthrough time (maximum wearing time) 480 min. Thickness of the glove material: 0,45 mm

#### Skin protection

Wear suitable gloves. Flame-retardant protective clothing. Wear anti-static footwear and clothing Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Respiratory protection necessary at: exceeding exposure limit values.

Suitable respiratory protection apparatus: Combination filtering device (EN 14387)

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

#### **Environmental exposure controls**

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

**Test method** 

Print date: 17.01.2020

pH-Value: not determined DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

-40 °C

Flash point:

-80 °C

**Flammability** 

Solid: not applicable
Gas: not applicable

# **Explosive properties**

Heating may cause an explosion. Vapours can form explosive mixtures with air.

Lower explosion limits: 0,9 vol. % Upper explosion limits: 15 vol. %

**Auto-ignition temperature** 

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 6 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,853 g/cm³ DIN 51757

Water solubility:

The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient:

Viscosity / dynamic:

viscosity / kinematic:

not determined

vapour density:

not determined

not determined

not determined

not determined

not determined

9.2. Other information

Odour threshold: not determined.

Relative density, Colour, Odour, Viscosity, pH: Data apply to the technically active substance.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Extremely flammable aerosol.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

# 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Protect against direct sunlight. Protect against: Frost. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic (Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black)

#### **Further information**

Do not mix with other chemicals.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 7 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

# **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
8042-47-5	White mineral oil (petroleum)					
	oral	LD50 > 5 mg/kg	5000	Rat	Manufacturer	
	dermal	LD50 > 2 mg/kg	2000	Rabbit	Manufacturer	
	inhalation (4 h) aerosol	LC50 > 5 mg/l	5000	Rat	Manufacturer	

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
8042-47-5	White mineral oil (petroleum)						
	Acute fish toxicity	LC50 mg/l	> 100		Brachydanio rerio (zebra-fish)	Manufacturer	
	Acute algae toxicity	ErC50 mg/l	> 100	1	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 mg/l	> 100		Daphnia magna (Big water flea)	Manufacturer	

# 12.2. Persistence and degradability

The product has not been tested.

# 12.3. Bioaccumulative potential

The product has not been tested.

# K4VO Dental Excellence

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Page 8 of 11

Revision date: 29.11.2019

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
75-28-5	isobutane	1,09
8042-47-5	White mineral oil (petroleum)	> 3,5
74-98-6	propane	1,09

#### 12.4. Mobility in soil

The product has not been tested.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

## **Further information**

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

# List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

## List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

# Contaminated packaging

Dispose of waste according to applicable legislation.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2

14.4. Packing group:

Hazard label: 2.1



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



Page 9 of 11

Revision date: 29.11.2019

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006

Page 10 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII): Entry 3: White mineral oil (petroleum) Entry 40: butane; isobutane; propane

2010/75/EU (VOC): 80 - 90 %

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

**Additional information** 

To follow: 2008/47/EC

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

## Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# **Safety Data Sheet**



according to Regulation (EC) No 1907/2006 Page 11 of 11

Revision date: 29.11.2019

Print date: 17.01.2020

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

# Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

# Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

## **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)